Eaton Ellipse PRO 650 DIN gruppo di continuità (UPS) A linea interattiva 0,65 kVA 400 W 4 presa(e) AC





Marchio : Eaton

Codice prodotto: ELP650DIN

Nome del prodotto : Ellipse PRO 650 DIN

Ellipse PRO 650 DIN

Eaton Ellipse PRO 650 DIN gruppo di continuità (UPS) A linea interattiva 0,65 kVA 400 W 4 presa(e) AC:

Ellipse PRO 650–1600VA è un UPS line-interactive sviluppato specificatamente per proteggere le workstation per applicazioni impegnative. Ellipse PRO è dotato di un display LCD che fornisce informazioni sullo stato del sistema e misurazioni in tempo reale. Dispone inoltre di uscite di potenza EcoControl che permettono un risparmio energetico fino al 20% e di una funzione ASR (Advanced Surge Reduction) pienamente conforme ai requisiti della norma IEC 616431-1.
Eaton Ellipse PRO 650 DIN. Topologia UPS: A linea interattiva, Potenza in uscita: 0,65 kVA, Potenza in uscita: 400 W. Tipo di uscita AC: Tipo F, Presa di corrente: Accoppiatore C14, Quantità prese AC: 4 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Tempo di salvataggio minimo a mezzo carico: 9 min. Fattore di forma: Tower, Colore del prodotto: Nero, Capacità di rack: 2U. Sicurezza: IEC/EN 62040-1, IEC/EN 62040 -2, CB, CE

Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	0,65 kVA
Potenza in uscita *	400 W
Tensione operativa in entrata (min) *	150 V
Tensione operativa in entrata (max) *	285 V
Frequenza di ingresso *	50/60 Hz
Tensione operativa di uscita (min)	220 V
Tensione di uscita (max)	240 V
frequenza output	50 Hz
Spegnimento di emergenza (EPO)	✔
Protezione contro le sovratensioni	✔
Caratteristiche della protezione contro le sovratensioni	Fax, Modem, Rete, Telefono

Connettività	
Tipo di uscita AC	Tipo F
Presa di corrente	Accoppiatore C14
Quantità prese AC	4 presa(e) AC
Quantità porte USB 2.0	1
Porta modem (RJ-11)	1
Quantità porte Ethernet LAN (RJ-45)	1

Batteria	
Tecnologia batteria	Acido piombo (VRLA)
Tempo di salvataggio minimo a mezzo carico	9 min
Batteria scambio a caldo	✘
test automatico batteria	✔
Partenza a freddo	✔

Design	
Fattore di forma *	Tower
Capacità di rack	2U
Colore del prodotto *	Nero
Tipo di display	LCD
Indicatori LED	✔

Safety regulation & standards	
Sicurezza	IEC/EN 62040-1, IEC/EN 62040 -2, CB, CE

Dimensioni e peso	
Larghezza	82 mm
Profondità	285 mm
Altezza	260 mm
Peso	6,6 kg

Dati logistici	
Codice del Sistema Armonizzato (SA)	85078000

Altre caratteristiche	
Voltaggio nominale di entrata	230 V

0743172437266

743172437266

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date