TP-Link Archer C80 router wireless Gigabit Ethernet Dual-band (2.4 GHz/5 GHz) Nero





Marchio : TP-Link

Codice prodotto: ARCHER C80

Nome del prodotto : Archer C80

TP-Link Archer C80. Tipo di connessione WAN: RJ-45. Banda Wi-Fi: Dual-band (2.4 GHz/5 GHz), Wi-Fi standard: Wi-Fi 5 (802.11ac), Intervallo di trasferimento dei dati WLAN (max): 1300 Mbit/s. Tipo di interfaccia LAN Ethernet: Gigabit Ethernet, Velocità trasferimento Ethernet LAN: 10,100,1000 Mbit/s, Tecnologia di cablaggio: 10/100/1000Base-T(X). Algoritmi di sicurezza supportati: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK. Tipo di prodotto: Router da tavolo, Colore del prodotto: Nero, Indicatori LED: LAN, Potenza, status, WLAN, WPS

Connessione WAN	
WAN Ethernet *	✔
Slot per scheda SIM *	✘
Tipo di connessione WAN	RJ-45
Caratteristiche Wireless LAN	
Banda Wi-Fi *	Dual-band (2.4 GHz/5 GHz)
Wi-Fi standard *	Wi-Fi 5 (802.11ac)
Intervallo di trasferimento dei dati WLAN (max) *	1300 Mbit/s
Standard Wi-Fi	802.11a, 802.11b, 802.11g, Wi-Fi 4 (802.11n), Wi-Fi 5 (802.11ac)
Frequenza di trasferimento dati WLAN (prima banda)	1300 Mbit/s
Collegamento in rete	
Collegamento ethernet LAN *	✔
Tipo di interfaccia LAN Ethernet *	Gigabit Ethernet
Velocità trasferimento Ethernet LAN	10,100,1000 Mbit/s
Tecnologia di cablaggio	10/100/1000Base-T(X)
Standard di rete	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Port forwarding	✔
DNS Dinamico (DDNS)	✔
Connettività	
Quantità porte Ethernet LAN (RJ-45) *	5
Porta USB *	✘
Slot per la scheda di memoria	✘
Jack DC-in	✔
Caratteristiche di gestione	
Tasto reset	✔
Sicurezza WPS Push Button	✔

Protocolli	
Cliente DHCP	✔
Server DHCP	✔
Universal Plug and Play (UPnP)	✔
Design	
Colore del prodotto	Nero
Montabile a parete	✔
Indicatori LED	LAN, Potenza, status, WLAN, WPS
Interrutore On/Off	✔
Tipo di prodotto *	Router da tavolo
Contenuto dell'imballo	
Cavi inclusi	AC, LAN (RJ-45)
Adattatore AC/DC	✔
Guida d'installazione rapida	✔
Antenna	
Design dell'antenna *	Esterno
Qualità dell'antenna	4
Antenna/Antenne staccabile/staccabili	✘
Potenza di trasmissione	CE: <20dBm(2.4 GHz), <23dBm(5.15 GHz~5.25 GHz), FCC:<30dBm(2.4 GHz & 5 GHz)
Gestione energetica	
Tipologia alimentazione *	dC
Voltaggio di uscita	12 V
Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Intervallo di temperatura	-40 - 70 °C
Range di umidità di funzionamento	10 - 90%
Umidità	5 - 90%

Sicurezza	
Algoritmi di sicurezza supportati	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK
Firewall	✔
Accesso ospite	✔
Lista di controllo accesso (ACL)	✔
Filtraggio stateful dei pacchetti (SPI)	✔
Filtri MAC address	✔
Supporto DMZ	✔

Requisiti di sistema	
Browser supportati	Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0
Sistema operativo Windows supportato	Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64, Windows 7, Windows 7 Enterprise, Windows 7 Enterprise x64, Windows 7 Home Basic, Windows 7 Home Basic x64, Windows 7 Home Premium, Windows 7 Home Premium x64, Windows 7 Professional, Windows 7 Professional x64, Windows 7 Starter, Windows 7 Starter x64, Windows 7 Ultimate, Windows 7 Ultimate x64, Windows 7 x64, Windows 8, Windows 8 Enterprise, Windows 8 Enterprise x64, Windows 8 Pro, Windows 8 Pro x64, Windows 8 x64, Windows 8.1, Windows 8.1 Enterprise, Windows 8.1 Enterprise x64, Windows 8.1 Pro, Windows 8.1 Pro x64, Windows 8.1 x64, Windows 98SE, Windows NT, Windows Vista, Windows Vista Business, Windows Vista Business x64, Windows Vista Enterprise, Windows Vista Enterprise x64, Windows Vista Home Basic, Windows Vista Home Basic x64, Windows Vista Home Premium, Windows Vista Home Premium x64, Windows Vista Ultimate, Windows Vista Ultimate x64, Windows Vista x64, Windows XP, Windows XP Home, Windows XP Home x64, Windows XP Professional, Windows XP Professional x64
Sistema operativo Linux supportato	✔
Compatibilità sistema operativo Mac	MacOS
Compatibilità Mac	✔

Dati su imballaggio	
Larghezza imballo	350 mm
Profondità imballo	240 mm
Altezza imballo	82 mm
Peso dell'imballo	250 g

6935364088873

1210002615976

1210002615969

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date