Nilox NXGCLI12001X7V2 gruppo di continuità (UPS) A linea interattiva 1,2 kVA 840 W 2 presa(e) AC



Marchio : Nilox

Codice prodotto: NXGCLI12001X7V2

Nome del prodotto : NXGCLI12001X7V2

- Stabilizzazione Tensione tramite AVR
- 2 Prese d’uscita protette da blackout
- USB per collegamento al PC/Server
- Software di gestione UPS compatibile con Windows, Mac OS X (fino alla versione 10.8), Unix, Linux, ecc

UPS PREMIUM LINE INTERACTIVE 1200 VA

Nilox NXGCLI12001X7V2. Topologia UPS: A linea interattiva, Potenza in uscita: 1,2 kVA, Potenza in uscita: 840 W. Tipo di uscita AC: Tipo F, Presa di corrente: Accoppiatore C14, Quantità prese AC: 2 presa(e) AC. Capacità della batteria: 5 Ah, Voltaggio della batteria: 12 V, Numero di batterie incluse: 1 pz. Fattore di forma: Mini Tower, Colore del prodotto: Nero, Codice di protezione internazionale (IP): IP20. Certificazione: CE



Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	1,2 kVA
Potenza in uscita *	840 W
Forma d'onda *	Pseudo sine
Tensione operativa in entrata (min) *	173 V
Tensione operativa in entrata (max) *	276 V
Tensione operativa di uscita (min)	220 V
Tensione di uscita (max)	230 V
frequenza output	50/60 Hz
Regolatore automatico di tensione (AVR)	✔
Tempo di risposta	2 ms
Efficienza	95%
Emissione acustica	40 dB

Connettività	
Tipo di uscita AC	Tipo F
Presa di corrente	Accoppiatore C14
Quantità prese AC	2 presa(e) AC
Porta USB	✔

Batteria	
Capacità della batteria	5 Ah
Voltaggio della batteria	12 V
Numero di batterie incluse	1 pz
Tempo di salvataggio minimo a pieno carico	7 min
Tempo di salvataggio minimo a mezzo carico	10 min
Tempo di ricarica	8 h

Design	
Fattore di forma *	Mini Tower
Colore del prodotto *	Nero
Codice di protezione internazionale (IP)	IP20

Certificati di sicurezza	
Certificazione	CE

Dimensioni e peso	
Larghezza	101 mm
Profondità	279 mm
Altezza	142 mm
Peso	4,5 kg

Dati su imballaggio	
Larghezza imballo	140 mm
Profondità imballo	220 mm
Altezza imballo	324 mm

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date

8051122173655

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date