APC BK350G2I gruppo di continuità (UPS) A linea interattiva 0,35 kVA 210 W 6 presa(e) AC



Marchio : APC

Codice prodotto: BK350G2I

Nome del prodotto : BK350G2I

APC BK350G2I. Topologia UPS: A linea interattiva, Potenza in uscita: 0,35 kVA, Potenza in uscita: 210 W. Tipo di uscita AC: Accoppiatore C13, Quantità prese AC: 6 presa(e) AC. Tecnologia batteria: Piombo-Acido, Capacità della batteria: 83 Ah, Durata della batteria (max): 5 anno/i. Fattore di forma: Tower, Colore del prodotto: Nero, Lunghezza cavo: 1,5 m. Certificati di conformità: CE, Certificazione: CE



Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	0,35 kVA
Potenza in uscita *	210 W
Forma d'onda *	Sinusoide simulata
Tensione operativa in entrata (min) *	176 V
Tensione operativa in entrata (max) *	294 V
Frequenza di ingresso *	50/60 Hz
Tensione operativa di uscita (min)	230 V
Tensione di uscita (max)	230 V
frequenza output	47/63 Hz
Valutazione sovraccarico energetico	1080 J
Tempo di risposta	8 ms
Emissione acustica	45 dB

Connettività	
Tipo di uscita AC	Accoppiatore C13
Quantità prese AC	6 presa(e) AC
Porta USB	✔

Batteria	
Tecnologia batteria	Piombo-Acido
Capacità della batteria	83 Ah
Durata della batteria (max)	5 anno/i
Tempo di ricarica	8 h

Design	
Fattore di forma *	Tower
Lunghezza cavo	1,5 m
Colore del prodotto *	Nero
Tipo di display	LED
Indicatori LED	Sostituzione della batteria, Guasto, status

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Intervallo di temperatura	-15 - 45 °C
Range di umidità di funzionamento	0 - 95%
Umidità	0 - 95%
Altitudine di funzionamento	0 - 3000 m

Certificati di sicurezza	
Certificati di conformità	CE
Certificazione	CE

Dimensioni e peso	
Larghezza	91 mm
Profondità	310 mm
Altezza	190 mm
Peso	6,1 kg

Dati su imballaggio	
Larghezza imballo	163 mm
Profondità imballo	395 mm
Altezza imballo	280 mm
Peso dell'imballo	7,3 kg

0731304792048

731304792048

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date