Eaton 3P Ellipse UPS gruppo di continuità (UPS) Standby (Offline) 1,3 kVA 840 W 8 presa(e) AC



Marchio : Eaton

Codice prodotto: 3P1300UI

Nome del prodotto : 3P Ellipse UPS

Eaton 3P Ellipse UPS. Topologia UPS: Standby (Offline), Potenza in uscita: 1,3 kVA, Potenza in uscita: 840 W. Tipo di uscita AC: Accoppiatore C13, Quantità prese AC: 8 presa(e) AC. Capacità della batteria: 7 Ah, Voltaggio della batteria: 12 V. Fattore di forma: Tower, Colore del prodotto: Nero, Tipo di controllo: Pulsanti. Certificati di conformità: CB, CE, RoHS, WEEE, Certificazione: IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 CE UKCA Ukr Cm



Caratteristiche	
Topologia UPS *	Standby (Offline)
Potenza in uscita *	1,3 kVA
Potenza in uscita *	840 W
Forma d'onda *	Graduale
Tensione operativa in entrata (min) *	161 V
Tensione operativa in entrata (max) *	284 V
Frequenza di ingresso *	46/70 Hz
Tensione operativa di uscita (min)	161 V
Tensione di uscita (max)	284 V
frequenza output	50/60 Hz
Consumo di energia (funzionamento medio)	26 W
Numero di fasi di ingresso	1
Numero di fasi di uscita	1
Efficienza	97%
Efficienza (modalità ECO)	97%
Fattore di potenza in uscita	0,6
Emissione acustica	25 dB
Protezione contro le sovratensioni	✔
Spegnimento automatico	✔

Connettività	
Tipo di uscita AC	Accoppiatore C13
Quantità prese AC	8 presa(e) AC
Porta USB	✔
Quantità porte USB 2.0	2
Quantità porte Ethernet LAN (RJ-45)	1

Batteria	
Capacità della batteria	7 Ah
Voltaggio della batteria	12 V

Design	
Fattore di forma *	Tower
Colore del prodotto *	Nero
Tipo di controllo	Pulsanti
Tipo di display	LED

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C

Certificati di sicurezza	
Conformità ai rifiuti di apparecchiature elettriche ed elettroniche (WEEE)	✔
Certificati di conformità	CB, CE, RoHS, WEEE
Certificazione	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 CE UKCA Ukr Cm

Contenuto dell'imballo	
Cavi inclusi	Cavo USB
Guida d'installazione rapida	✔

Dimensioni e peso	
Larghezza	81 mm
Profondità	312 mm
Altezza	305 mm
Peso	7 kg

Dati su imballaggio	
Tipo di imballo	Scatola

Altre caratteristiche	
Tipo connessione ingresso	C14
Voltaggio nominale di entrata	220-240 V
Umidità relativa	0 - 95%

3553340621406

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date