APC Easy UPS gruppo di continuità (UPS) A linea interattiva 1,2 kVA 650 W 4 presa(e) AC



Marchio : APC

Codice prodotto: BVX1200LI-GR

Nome del prodotto : Easy UPS

APC Easy UPS. Topologia UPS: A linea interattiva, Potenza in uscita: 1,2 kVA, Potenza in uscita: 650 W. Tipo di uscita AC: Tipo F, Presa di corrente: Tipo F, Quantità prese AC: 4 presa(e) AC. Tecnologia batteria: Acido piombo (VRLA), Capacità della batteria: 9 Ah, Voltaggio della batteria: 12 V. Colore del prodotto: Nero, Lunghezza cavo: 1,2 m, Codice di protezione internazionale (IP): IP20. Certificazione: CE, EN/IEC 62040-1, EN/IEC 62040-2



Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	1,2 kVA
Potenza in uscita *	650 W
Forma d'onda *	Sinusoidale
Tensione operativa in entrata (min) *	140 V
Tensione operativa in entrata (max) *	300 V
Frequenza di ingresso *	50/60 Hz
frequenza output	50/60 Hz
Regolatore automatico di tensione (AVR)	✔
Valutazione sovraccarico energetico	273 J
Tempo di risposta	6 ms
Allarmi sonori	✔

Connettività	
Tipo di uscita AC	Tipo F
Presa di corrente	Tipo F
Quantità prese AC	4 presa(e) AC
SmartSlot	✘
Porta SmartConnect	✘

Batteria	
Tecnologia batteria	Acido piombo (VRLA)
Capacità della batteria	9 Ah
Voltaggio della batteria	12 V
Durata della batteria (max)	3 anno/i
Tempo di ricarica	8 h
Partenza a freddo	✔

Design	
Colore del prodotto *	Nero
Indicatori LED	✔
Codice di protezione internazionale (IP)	IP20

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Intervallo di temperatura	-15 - 40 °C
Range di umidità di funzionamento	0 - 95%
Altitudine di funzionamento	0 - 3000 m
Altitudine di non-funzionamento	0 - 3000 m

Certificati di sicurezza	
Certificazione	CE, EN/IEC 62040-1, EN/IEC 62040-2

Contenuto dell'imballo	
Cavi inclusi	Cavo di alimentazione di ingresso
Scheda di gestione inclusa	✘

Dimensioni e peso	
Larghezza	140 mm
Profondità	390 mm
Altezza	190 mm
Peso	7,5 kg

Dati su imballaggio	
Larghezza imballo	495 mm
Profondità imballo	235 mm
Altezza imballo	297 mm
Peso dell'imballo	8,5 kg

Design		Dati logistici	
Lunghezza cavo	1,2 m	Codice del Sistema Armonizzato (SA)	85078000



0731304404606



731304404606

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date