FSP FP 1500 gruppo di continuità (UPS) A linea interattiva 1,5 kVA 900 W 4 presa(e) AC





Marchio : FSP

Codice prodotto: PPF9000501

Nome del prodotto : FP 1500

FSP FP 1500. Topologia UPS: A linea interattiva, Potenza in uscita: 1,5 kVA, Potenza in uscita: 900 W. Tipo di uscita AC: Tipo F, Quantità prese AC: 4 presa(e) AC. Capacità della batteria: 9 Ah, Voltaggio della batteria: 12 V, Tempo di ricarica: 6 h. Fattore di forma: Mini Tower, Colore del prodotto: Nero. Certificati di conformità: CE, EAC

Caratteristiche	
Topologia UPS *	A linea interattiva
Potenza in uscita *	1,5 kVA
Potenza in uscita *	900 W
Forma d'onda *	Sinusoidale
Tensione operativa in entrata (min) *	162 V
Tensione operativa in entrata (max) *	290 V
Frequenza di ingresso *	50/60 Hz
Tensione operativa di uscita (min)	100 V
Tensione di uscita (max)	240 V
frequenza output	50/60 Hz
Regolazione della tensione di uscita	10%
Regolatore automatico di tensione (AVR)	✔
Tempo di risposta	6 ms
Emissione acustica	40 dB
Funzionalità di protezione dell'alimentazione	Scarica della batteria, Sovraccarico, Sovraccarico
Allarmi sonori	✔
Modalità allarme acustici	Allarme in funzionamento a batteria, Guasto, Allarme per batteria scarsa, Allarme di sovraccarico
Riavvio automatico	✔

Connettività	
Tipo di uscita AC	Tipo F
Quantità prese AC	4 presa(e) AC

Batteria	
Tempo di ricarica della batteria (90%)	6 h
Partenza a freddo	✔
Carica in modalità off	✔

Design	
Fattore di forma *	Mini Tower
Colore del prodotto *	Nero
Indicatori LED	✔

Condizioni ambientali	
Intervallo temperatura di funzionamento	0 - 40 °C
Range di umidità di funzionamento	0 - 90%

Certificati di sicurezza	
Certificati di conformità	CE, EAC

Contenuto dell'imballo	
Manuale dell'utente	✔

Sostenibilità	
Conformità alla sostenibilità	✔

Dimensioni e peso	
Larghezza	130 mm
Profondità	320 mm
Altezza	182 mm
Peso	10,4 kg

Batteria	
Capacità della batteria	9 Ah
Voltaggio della batteria	12 V
Numero di batterie	2
Tempo di ricarica	6 h

Dati su imballaggio	
Larghezza imballo	190 mm
Profondità imballo	390 mm
Altezza imballo	275 mm
Tipo di imballo	Scatola

Dati logistici	
Codice del Sistema Armonizzato (SA)	85078000

4711140487656

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 17-NOV-2026. Prints or copies of Information are only valid on the printed Publication date