TP-Link Omada EAP683 UR punto accesso WLAN 4804 Mbit/s Bianco Supporto Power over Ethernet (PoE)



Marchio : TP-Link

Famiglia del prodotto: Omada

Codice prodotto: EAP683 UR

Nome del prodotto : EAP683 UR

TP-Link Omada EAP683 UR. 2.4 GHz, 5 GHz, Velocità massima di trasferimento dati: 4804 Mbit/s. Algoritmi di sicurezza supportati: WPA, WPA2, WPA3. Velocità trasferimento Ethernet LAN: 10,100,1000,2500 Mbit/s. Supporto Power over Ethernet (PoE). Colore del prodotto: Bianco



Caratteristiche	
2.4 GHz *	✔
5 GHz *	✔
6 GHz *	✘
Velocità massima di trasferimento dati *	4804 Mbit/s
Velocità massima di trasferimento dati (2,4 GHz)	1148 Mbit/s
Velocità massima di trasferimento dati (5 GHz)	4804 Mbit/s
Velocità trasferimento Ethernet LAN	10,100,1000,2500 Mbit/s
Banda di frequenza	2.4 - 6 GHz
Standard di rete	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at
Numero di utenti	510 utente(i)
Selezione automatica dei canali	✔
Scansione canale automatica	✔
MIMO	✔
Tipo MIMO	Multi User MIMO
Roaming veloce	✔
VLAN support	✔
Limitazione della velocità	✔
Direzione della banda	✔
Airtime Fairness (ATF)	✔
Supporto qualità del servizio (QoS)	✔
BeamForming	✔

Sicurezza	
Algoritmi di sicurezza supportati *	WPA, WPA2, WPA3
Filtri MAC address	✔
Funzioni SSID (Service Set Identifier)	Multiple SSIDs

Caratteristiche di gestione	
Firmware aggiornabile	✔

Connettività	
Quantità porte Ethernet LAN (RJ-45) *	1
Jack DC-in	✔

Gestione energetica	
Supporto Power over Ethernet (PoE) *	✔
tasso di voltaggio DC	12 V

Design	
Installazione *	Soffitto, Parete
Colore del prodotto *	Bianco
Tasto reset	✔
Indicatori LED	✔

Antenna	
Tipo di antenna *	Interno
Tipo di direzione dell'antenna	Omnidirezionale
Livello di guadagno dell'antenna (max)	5 dBi

Dimensioni e peso	
Larghezza	220 mm
Profondità	220 mm
Altezza	32,5 mm

Dati su imballaggio	
Tipo di imballo	Scatola

Contenuto dell'imballo	
Quantità per pacco	1 pz
Kit di montaggio	✔
Guida rapida	✔

Sicurezza	
Lista di controllo accesso (ACL)	✔

Caratteristiche di gestione	
Syslog	✔

Condizioni ambientali	
Range di umidità di funzionamento	10 - 90%
Intervallo temperatura di funzionamento	0 - 40 °C
Intervallo di temperatura	-40 - 70 °C
Umidità	5 - 90%

8885020621938

0810142821018

810142821018

8885020621945

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 11-NOV-2026. Prints or copies of Information are only valid on the printed Publication date